LA Audio P-845

MONO POWER AMPLIFIER





LA AUDIO ELECTRONIC CO., LTD

9F-1 NO. 37 HSI TSARNG ROAD TAIPEI TAIWAN WWW. laaudio. com. tw TEL:+886-2-23092540 FAX:+886-2-23091615 READ THIS MANUAL CAREFULLY BEFORE YOU USE THIS VACUUM TUBE AMPLIFIER KEEP IT FOR FUTURE USE.

A WARNING

- To prevent fire or shock hazards, Do not expose the unit to rain or moisture.
- To avoid electrical shock, Do not open the case. Refer to certificated professional only. For your safety, please pay attention to the marks of safety and the advise of preventing electricity.


Advice of LA-AUDIO

This machine is designed based on original circuit of vacuum tube, and all of compounds were designed based on the requirement of the highvoltageas well. The modification is not allowed for any reason, we will not accept any modified machine for the warranty.

Operating Instruction


Before operating the machine, please check the voltage whether conforms to your demands. Please select your needed voltage for 230V or 115V. Plug the electron tube to the specified outlet according to following drawing number.Connect the loudspeaker and the output terminal of the machine and the signal cord at the same time. Then turn on the machine, if there is any anomalism occurred while the machine is operating, (EX: smoking, peculiar smell and vacuum.... etc) please turn off the power and contact to your dealer or our company immediately.

CONTROLS




FRONT PANEL


1. POWER SWITCH 2. INDICATOR



AC POWER INPUT JACK
CHANNEL OUTPUT TERMINAL

CONNECTION





VACUUM TUBE POSITION

REAR PANEL

3. RCA SIGNAL TERMINAL

A: POWER TRANSFORMER B: OUTPUT TRANSFORMER C: CONDENSER V1:6SL7 V2: 6SN7 V3: 300B V4:845

SPECIFICATIONS

- 1. POWER: 230V/115V 50Hz/60Hz
- 2. OUTPUT POWER: 35W
- 3. FREQUENCY RESPONSE: 20Hz-28KHz
- 4. SIGNAL TO NOISE RATIO:85dB
- 5. OUTPUT IMPEDANCE: $0 \Omega 4 \Omega 8 \Omega$
- 6. TOTAL HARMONIC DISTORTION: $\leq 1.5\%$ (1KHz)
- 7. CONSUMED POWER: 190W
- 8. VACUUM TUBE: 6SL7 1 6SN7 1 300B 1 845 1
- 9. DIMENSIONS W D H(CM): 30 47 21 10. WEIGHT: 17Kg